

76

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: **58093866 A**

(43) Date of publication of application: **03.06.83**

(51) Int. Cl

**C23C 7/00**  
**C23D 7/00**

(21) Application number: **56191826**

(22) Date of filing: **01.12.81**

(71) Applicant: **AGENCY OF IND  
SCIENCE & TECHNOL**

(72) Inventor: **NAKABASHI MASAOKO  
TAKEDA HIROMITSU  
BABA HIDEKAZU  
SUZUKI TAKAO**

(54) **METHOD FOR PREVENTING SURFACE FROM  
DAMAGE**

(57) Abstract:

PURPOSE: To obtain a masking coat which is stable even in an atmosphere at high temp. and can be easily stripped after use, by coating  $Al_2O_3$  or  $ZrO_2$  as a porous inorg. substance stuck to a part to be masked with a high m.p. metallic layer contg. Ni or Cr.

CONSTITUTION:  $Al_2O_3$  and/or  $ZrO_2$  as a porous inorg. substance is stuck to a part to be masked. The surface of the inorg. substance is coated with a high m.p. metallic layer of Ni, Cr or an alloy thereof. Thus, a masking coat which is stable even in an atmosphere at high temp. and is easily stripped after use is obtd.

COPYRIGHT: (C)1983,JPO&Japio

**BEST AVAILABLE COPY**